

Two 6.4" LCD rack, composite

Ref: 064RK02VFA



GENERAL SPECIFICATIONS

LCD type	6.4" TFT active matrix
Cabinet	19" rack 3ru height
Units in rack	2 LCD-TFT
Controls	Analogue front controls
Tilting angle	+50° / -50°

DISPLAY

Brightness	330 cd/m2
Contrast ratio	350:1
Resolution (dots)	960(h) x 234(v)
Pixel	0.135(h) x 0.416(v) mm
Viewing angle	40°/55°(u/d), 60°/60°(l/r)
Viewing area	129.6(h) x 97.34(v) mm
Lamp life	30,000 hrs

INPUTS & OUTPUTS - EACH DISPLAY

Data input	Not available
Video input	BNC video composite (2 input , 1 Vpp 75Ω EN50049, NFC92250) PAL/NTSC Auto Detect
Video output	BNC video composite (2 Output)
Tally	2xLed - D-Sub 9 pins (contact close)

ELECTRICAL


TFT power supply	12Vdc, 1.3 A
Rack power supply	100-240 Vac, 47-63 Hz, 12V 3.3 A
Power consumption	16 W

MECHANICAL

Rack dimensions	480 x 132.5 x 71.5 mm
Weight	3.4 Kg

OTHER

Response time	Tr 15 ms, Tf 25 ms
Temperature	Operating +0°C ~ +60°C, Storage -25°C ~ +80°C



Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL



ALBIRAL DISPLAY SOLUTIONS SL
C/ Fàtima 25, 08512 Sant Hipòlit de Voltregà
Barcelona - Spain
Tel.: +34 93 850 23 76 / 23 83
fax: +34 93 850 25 50
web: www.albiral.com
e-mail: marketing@albiral.com

ALBIRAL PRO, S.L.
C/ Vázquez de Mella 23,
28017 Madrid - Spain
tel: +34 91 368 11 90
fax: +34 91 368 11 97
web: www.albiral.com
e-mail: albiral@albiral.com

www.albiral.com