

7" 16:9 composite monitor, adaptable to external batteries

Ref:070SC01VT



GENERAL SPECIFICATIONS

LCD type	7" TFT Active Matrix 16:9 format
Cabinet	Handheld with sun hood (screw mounting)
Units in rack	1 LCD-TFT
Controls	Analogue front controls

DISPLAY

Brightness	400 cd/m ²
Contrast ratio	350:1
Resolution (dots)	480(h) x RGB x 234(v)
Pixel	0.321(h) x 0.372(v) mm
Viewing angle	40°/50°(u/d), 60°/60°(l/r)
Viewing area	154.08(h) x 87.05(v) mm
Lamp life	40,000 hrs

INPUTS & OUTPUTS

Data input	Not available
Video input	BNC video composite (2 input A/B 1Vpp 75Ω) PAL/SECAM/ NTSC Auto Detect
Video output	BNC video composite (1 output)
Tally	LED Mini jack (contact close)

ELECTRICAL

TFT power supply	12Vdc, 0.6 A
Rack power supply	100-240 Vac, 47-63 Hz, 12Vdc-3.3A
Power consumption	7W

MECHANICAL

Rack dimensions	174 x 131 x 47 mm
Weight	1.2Kg

OTHER

Response time	Tr15ms, Tf25ms
Temperature	Operating +0°C ~ +60°C, Storage -25°C ~ +80°C

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL



ALBIRAL DISPLAY SOLUTIONS SL
C/ Fàtima 25, 08512 Sant Hipòlit de Voltregà
Barcelona - Spain
Tel.: +34 93 850 23 76 / 23 83
fax: +34 93 850 25 50
web: www.albiral.com
e-mail: marketing@albiral.com

ALBIRAL PRO, S.L.
C/ Vázquez de Mella 23,
28017 Madrid - Spain
tel: +34 91 368 11 90
fax: +34 91 368 11 97
web: www.albiral.com
e-mail: albiral@albiral.com

www.albiral.com