



GENERAL SPECIFICATIONS

LCD Type	32" TFT Active Matrix 16:9
Cabinet	Metal vandal proof
Controls	Digital internal
Speakers	2 x 7W
Ventilation	Forced ventilation system

DISPLAY

Brightness	500cd/m2
Contrast ratio	1200:1
Resolution (dots)	WXGA 1366(h) x 768(v)
Pixel	0.6(h) x 0.6(v) mm
Viewing angle	88°/88°(U/D) / 88°/88°(L/R)
Viewing area	697.69 x 392.26 mm

OTHER

Response time	Tr+Tf 12ms, Tg 6ms
Temperature	Operating +5°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS

Data input	RGB SubD 15 (1 input) / DVI-D (1 input)
Video input	RGB BNC [R,G,B,H,V]/ component DVD, HD [Y, Pb/Cb, Pr/Cr] BNC & RCA vomposite video (1 input)/ S-VIDEO Mini din 4 (1 input)
Audio input	3 audio input, 1 x minijack, 2 x stereo RCA
Outputs	RGB SubD 15, BNC composite video, 2x RCA audio
RS232	External monitor control

ELECTRICAL

Power	100-240 Vac, 47/63Hz
Power consumption	170 W

MECHANICAL

Dimensions	981 x 516 x 181 mm
Weight	50Kg
VESA	200
Internal access door	Security close (key)

Especificaciones sujetas a modificaciones sin previo aviso. Albiral es una marca registrada por ALBIRAL DISPLAY SOLUTIONS SL



ALBIRAL DISPLAY SOLUTIONS SL
 C/ Fátima 25,
 08512 Sant Hipòlit de Voltregà
 Barcelona - Spain
 Tel.: +34 93 850 23 76 / 23 83
 fax: +34 93 850 25 50
 web: www.albiral.com
 e-mail: marketing@albiral.com

ALBIRAL PRO, S.L.
 C/ Vázquez de Mella 23,
 28017 Madrid - Spain
 tel: +34 91 368 11 90
 fax: +34 91 368 11 97
 web: www.albiral.com
 e-mail: albiral@albiral.com

www.albiral.com