



### GENERAL SPECIFICATIONS

LCD Type	42" TFT Active Matrix 16:9
Cabinet	Metal vandal proof
Controls	Digital internal
Speakers	2 x 7W
Ventilation	Forced ventilation system

### DISPLAY

Brightness	500cd/m <sup>2</sup>
Contrast ratio	1600:1
Resolution (dots)	WXGA 1366(h) x 768(v)
Pixel	0.681(h) x 0.681(v) mm
Viewing angle	89°/89°(U/D) / 89°/89°(L/R)
Viewing area	930(h) x 523(v) mm

### OTHER

Response time	Tg 9ms
Temperature	Operating +5°C ~ +35°C, Storage -20°C ~ +60°C

### INPUTS & OUTPUTS

Data input	RGB SubD 15 (1 input) / DVI-D (1 input)
Video input	RGB BNC [R,G,B,H,V]/ component DVD, HD [Y, Pb/Cb, Pr/Cr] BNC & RCA composite video (1 input)/ S-VIDEO Mini din 4 (1 input)
Audio input	3 audio input, 1 x minijack, 2 x stereo RCA
Outputs	RGB SubD 15, BNC composite video, 2x RCA audio
RS232	External monitor control

### ELECTRICAL

Power	100-240 Vac, 47/63Hz
Power consumption	230 W

### MECHANICAL

Dimensions	1250 x 665 x 167.5 mm
Weight	50Kg
VESA	200
Internal access door	Security close (key)

Especificaciones sujetas a modificaciones sin previo aviso. Albiral es una marca registrada por ALBIRAL DISPLAY SOLUTIONS SL